## WHAT IS CLAIMED IS:

- Fishing apparatus suited for being supported on a fishing tackle box pail or other selected sporting article comprising,
  - a support arm,
  - a fishing reel rotatably mounted at the free end of the support arm,
  - a mounting bracket,
  - a pivot connected between a proximal end of the support arm and the mounting bracket, said pivot including a releasable lock for holding the reel support arm in any of a plurality of selected positions so that the arm can be raised, extended horizontally or lowered to a downwardly extending position on the bracket and releasably held in any of said positions,
  - a support member,
  - a connector between the support member and the bracket and said bracket including a coupling member for connecting the bracket to one of said supporting articles.
- The apparatus of Claim 1 wherein the connector comprises a sliding connection wherein the bracket is adapted to slide vertically onto said support member for being suspended thereform.

- 3. The apparatus of Claim 2 wherein the sliding connection comprises a pivot pin extending from the support member.
- 4. The apparatus of Claim 2 wherein the support member includes an opening and the bracket includes an end portion adapted to be connected to the support member adjacent the opening..
- 5. The apparatus of Claim 1 wherein the sporting article comprises a tackle box having a plurality of said support members thereon for mounting the bracket thereupon in different locations on the tackle box.
- 6. The apparatus of Claim 1 wherein the pivot between the support arm and bracket includes a plurality of radially extending interfitting grooves and ridges surrounding the axis of the pivot and a resilient member for yieldably biasing the ridges into engagement with the grooves where thereby retaining the arm in any of said selected positions about said pivot.
- 7. The apparatus of Claim 1 wherein the support member is connected to a fishing tackle box, a vertically disposed pin extends from the support member and the bracket is pivotally mounted upon the pin whereby the bracket can be articulated about a vertical axis at the center of the pin and the arm can be raised and lowered to selected positions about said pivot between the bracket and the arm.

- 8. The apparatus of Claim 1 wherein the bracket is suspended from a support assembly, said support assembly comprises at least one arm that is removably connectable to the bracket for holding the bracket within an ice hole.
- 9. The apparatus of Claim 8 wherein the support assembly comprises a plurality of arms connected by a pivot and adapted to extend from said pivot radially for suspending the bracket, the arm and reel so as to extend downwardly through the ice hole.
- 10. A fishing apparatus for supporting a fishing rod and reel from a receptacle having sidewalls and an upper open wide mouth said apparatus comprising, a support member on the side wall of the receptacle, a bracket removeably mounted on the support member, an arm pivotally connected to the bracket, a releasable lock as part of the pivot for releasably supporting the arm in any of the plurality of selected positions about the axis of said pivot, said arm having a holder thereon for supporting a sporting article to hold the sporting article in a vertical position or a selected angle of inclination.
- 11. The apparatus of Claim 10 wherein the arm includes a hollow tubular portion that is open at a free end thereof for receiving the handle of a fishing rod.
- 12. The apparatus of Claim 11 wherein the pivot between the support arm and bracket comprises a plurality of radially extending interfitting grooves and

ridges surrounding the axis of the pivot and a resilient member for yieldably biasing the ridges into engagement with the grooves to thereby retain the arm in any of a plurality of selected positions about said pivot.